## **LISTING OF THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

# Claims 1-14 (Canceled)

## Claim 15 (Currently Amended)

An apparatus for polishing side faces of grooves formed on a workpiece comprising:

- a fixture for fixing the workpiece;
- a rotating shaft disposed in a horizontal direction of the fixture;
- a rotary driving unit for rotating the rotating shaft;
- a disc polishing element having abrasive grains thereon for polishing the side faces of the grooves, the polishing element being fixed to the rotating shaft;

wherein said disk polishing element has said abrasive grains on a side face thereof for polishing said workpiece, and said disk polishing element further comprises abrasive grains at a peripheral edge thereof for cutting said workpiece;

a driving unit for driving moving at least one of the rotating shaft and the workpiece in the vertical direction of the rotating shaft, horizontally in the horizontal longitudinal direction of the rotating shaft, and in the transverse direction along the side face of the grooves; and

a detector for detecting the position where the polishing element is in contact with the workpiece.

### Claim 16 (Original)

An apparatus according to claim 15, wherein said abrasive grains on said disk polishing element have a cutting depth of about 10nm or less.

-3-

### Claim 17 (Canceled)

00727622.1

and the control of th

#### Claim 18 (Currently Amended)

An apparatus for polishing side faces of grooves formed on a workpiece comprising:

a fixture for fixing the workpiece;

a rotating shaft disposed in a horizontal direction of the fixture;

a rotary driving unit for rotating the rotating shaft;

a disc polishing element having abrasive grains thereon for polishing the side faces of the grooves, the polishing element being fixed to the rotating shaft;

wherein said disk polishing element has said abrasive grains on a side face thereof for polishing said workpiece, and said disk polishing element further comprises abrasive grains at a peripheral edge thereof for cutting said workpiece;

a driving unit for moving at least one of the rotating shaft and the workpiece in the vertical direction, horizontally in the longitudinal direction of the rotating shaft, and in the transverse direction along the side face of the grooves; and

a detector for detecting the position where the polishing element is in contact with the workpiece.

An apparatus according to claim 15, further comprising a sensor for detecting said contact position by detecting an electrical characteristic of said rotary driving unit, said electrical characteristic comprising at least one of a magnetic field and a current of said rotary driving unit.

## Claim 19 (Original)

An apparatus according to claim 18, wherein said sensor is a Hall sensor.

## Claim 20 (Original)

An apparatus according to claim 15, wherein said driving unit drives said at least one of the rotating shaft and the workpiece using said detected contact position as a reference.

### Claim 21 (New)

An apparatus according to claim 18, wherein said abrasive grains on said disk polishing element have a cutting depth of about 10nm or less.

00727622.1